

AMENDMENTS TO THE CLAIMS

This listing of the claims replaces all prior versions, and listings of the claims in the application:

1-7. (Canceled)

8. (Currently Amended) An apparatus for delivering pressurized gas to the airway of a patient, the apparatus comprising:

a housing;

a mounting surface disposed on the housing;

a blower assembly operatively coupled to the mounting surface and adapted to generate a flow of a pressurized gas;

a patient circuit coupled to the blower assembly and adapted to communicate the flow of gas to an airway of a patient;

a first vibration damping member disposed between a first side of the blower assembly and the mounting surface upon which the blower assembly is supported, the first vibration damping member being in contact with each of the first side of the blower assembly and the mounting surface so as to space the blower assembly from the mounting surface;

a securing member positioning and holding the blower assembly onto the mounting surface~~The apparatus of claim 7~~, wherein the securing member is a rigid member that includes:

a recess for receiving and locating a portion of the blower assembly and the second vibration damping member, and

at least two attaching legs extending to and fastened to the mounting surface; and

a second vibration damping member disposed between a second side of the blower assembly opposite the first side and the securing member, the second vibration damping member being in contact with each of the second side of the blower assembly and the securing member so as to space the blower assembly from the securing member.

9. (Original) The apparatus of claim 8, wherein the second vibration damping member includes a recess receiving a portion of the blower assembly.

10. (Original) The apparatus of claim 9, wherein the mounting surface is on a rigid mounting plate secured to the housing.

11. (Original) The apparatus of claim 10, further comprising an injection molded thermoplastic elastomeric tubular coupling between the blower assembly and the patient circuit.

12. (Original) The apparatus of claim 11, further comprising a valve attached to the mounting plate in fluid communication with the patient circuit, and an additional injection molded thermoplastic elastomeric member is positioned between the valve and the mounting plate.

13. (Canceled).

14. (Currently Amended) A vibration isolation mounting system for a blower assembly mounted in a housing, the system comprising:

a mounting surface supporting the blower assembly within a housing;

a first vibration damping member disposed between a first side of the blower assembly and the mounting surface, the first vibration damping member being in contact with at least a portion of each of the first side of the blower assembly and the mounting surface such that the blower assembly is spaced apart from the mounting surface by the first vibration damping member;

a securing member positioning and holding the blower assembly to the mounting surface~~The system of claim 13~~, wherein the securing member is a rigid member that includes:

a recess receiving and locating a portion of the blower assembly and the second vibration damping member, and

at least two attaching legs extending to and fastened to the mounting surface; and

a second vibration damping member disposed between a second side of the blower assembly opposite the first side and the securing member, the second vibration damping member being in contact with at least a portion of each of the second side of the blower assembly and the securing member such that the blower assembly is spaced apart from the securing member.

15. (Original) The system of claim 14, wherein the first and the second vibration damping members are injection molded thermoplastic elastomeric members.

16. (Original) The system of claim 15, wherein the mounting surface is on a rigid mounting plate secured to the housing.

17. (Original) The system of claim 16, further comprising an injection molded thermoplastic elastomeric coupling attached to the blower assembly.

18. (Original) The system of claim 15, wherein the thermoplastic elastomeric members are formed of a rubber compound of about 2.79 durometers.

19. (Original) The system of claim 15, further comprising an injection molded thermoplastic elastomeric tubular coupling attached to the blower assembly, wherein the tubular coupling includes a pair of end sections and an intermediate section with a wall thickness less than that of the end sections.

20. (Original) The system of claim 15, wherein at least one of the vibration damping members includes a recess for receiving a portion of the blower assembly.